

IN THE CLAIMS:

*Please substitute claims 1-28 with amended claims 1-28.*

1. (Amended) Device for the separation of plastic cards, especially chip cards, from a sheet or strip material, with an upper and lower cutting tool defining the cutting outline which are designed to cut into a corresponding upper and lower side of the sheet or strip material, while retaining a residual cross-piece, ~~characterized in that~~ wherein at least two upper and at least two lower cutting tools assigned in each case next to each other are provided for the forcibly coupled separation of several plastic cards.

2. (Amended) Device according to Claim 1, ~~characterized in that between~~ wherein, between an upper and a lower cutting tool a fixing device for the positioning and holding of the sheet or strip material is provided at least during the cutting process.

3. (Amended) Device according to Claim 2, ~~characterized in that~~ wherein the fixing device consists of an upper and a lower guide frame element.

4. (Amended) Device according to Claim 3, ~~characterized in that~~ wherein the guide frame elements of at least two adjacent cutting tools are linked to form a jointly movable guide frame element.

5. (Amended) Device according to Claim 4, ~~characterized in that~~ wherein the guide frame is spring supported.

6. (Amended) Device according to Claim 4 ~~or 5~~, ~~characterized in that~~ wherein the guide frame is formed as a single component.

7. (Amended) Device according to ~~one of the Claims 3 to 6~~,  
~~characterized in that~~ wherein the cutting tools each have a wedge-shaped cutting blade defining  
the cutting outline and the guide frame element assigned in each case has  
a window, whereby the cutting blade is formed such that it can move into the assigned window.

8. (Amended) Device according to Claim 7,  
~~characterized in that~~ wherein the guide frame has at least two adjacent windows which are  
separated from each other by connecting struts.

9. (Amended) Device according to Claim 8,  
~~characterized in that~~ wherein the connecting struts of the guide frame are formed as replaceable  
round bars.

10. (Amended) Device according to Claim ~~8 or 9~~,  
~~characterized in that~~ wherein the connecting struts have a width of 2 to 5 times the thickness of  
the plastic cards.

11. (Amended) Device according to ~~one of the Claims 1 to 10~~,  
~~characterized in that~~ wherein the cutting tools have a cutting outline running round in a rectangle  
with a longer and a shorter side and the shorter sides of the adjacent cutting tools are aligned  
parallel to each other.

12. (Amended) Device according to Claim 11,  
~~characterized in that~~ wherein between two adjacent wedge-shaped cutting blades a groove is  
formed to incorporate the connecting strut during the cutting process.

13. (Amended) Device according to Claim 12,  
~~characterized in that~~ wherein the depth of groove is greater than the height of the connecting  
struts.

14. (Amended) Device according to ~~one of the Claims 1 to 13~~,  
~~characterized in that~~ wherein at least one lower and/or one associated upper cutting tool is  
positioned on a base plate and this base plate has at least one window positioned coaxially to the  
cutting outline of a cutting tool, whereby the opening surface of the windows corresponds at least  
to the surface covered by the cutting outline.

15 (Amended) Device according to ~~one of the Claims 1 to 14~~ with a pressure stamp that can  
plunge into the cutting outline for separating out the cut plastic cards from the sheet or strip  
material, ~~characterized in that~~ wherein ventilation is provided for the air present or enclosed  
between the pressure stamp and the plastic card and that this is formed such that a pressure  
difference between the pressure of the air present between the pressure stamp and the plastic card  
during the separation process and the ambient pressure is limited to a predetermined value.

16. (Amended) Device according to Claim 15,  
~~characterized in that~~ wherein the ventilation to limit the value of the pressure difference to the  
ambient pressure is formed such that any disruptive influence of the air present or enclosed  
between the pressure stamp and the plastic card during separation of the plastic card is kept to a  
minimum.

17. (Amended) Device according to Claim 15 ~~or 16~~,  
~~characterized in that~~ wherein the ventilation is formed such that any suction effect from the  
pressure stamp on moving back after the separation of the plastic card is kept to a minimum.

18. (Amended) Device according to ~~one of the Claims 15 to 17~~,  
~~characterized in that~~ wherein the distance between the pressure stamp and the a wedge-shaped  
cutting blade during cutting ~~processes~~ processes less than the thickness of the plastic cards, and  
preferably less than 0.3 mm.

19. (Amended) Device according to ~~one of the Claims 15 to 18~~,  
~~characterized in that~~ wherein the pressure stamp has a front surface that is in contact with the plastic card during separation and is provided with at least one bored hole open to the front surface to provide ventilation.

20. (Amended) Device according to Claim 19,  
~~characterized in that~~ wherein the bored holes in the front surface are symmetrical to the longitudinal and transverse axes of the front surface running parallel to the side edges of the front surface.

21. (Amended) Device according to ~~one of the Claims 15 to 20~~,  
~~characterized in that~~ wherein the ventilation is provided by a three-dimensional contouring at the front surface.

22. (Amended) Device according to Claim 21,  
~~characterized in that~~ wherein raised corner areas of the front surface span jointly a conceived area, and ~~that~~ side edges in between are set back in relation to the conceived area.

23. (Amended) Device according to ~~one of the Claims 15 to 22~~,  
~~characterized in that~~ wherein the ventilation has at least one groove on the front surface.

24. (Amended) Device according to ~~one of the Claims 15 to 23~~,  
~~characterized in that~~ wherein the ventilation includes air ducts at the cutting tools.

25. (Amended) Method for the separation of plastic cards with ~~one of the devices from the Claims 1 to 24~~ with the following stages:

- ~~F~~ixing the sheet or strip material,
- ~~C~~utting the upper and lower side of the sheet or strip material with the assigned upper and lower cutting tools defining the cutting outline, while retaining a residual cross-piece;
- ~~P~~ressing out of the plastic cards from the sheet or strip material,

~~characterized in that~~ wherein at least two plastic cards are separated forcibly coupled out from the sheet or strip material at the same time.

26. (Amended) Method according to Claim 25,

~~characterized in that~~ wherein at least two plastic cards are fixed forcibly coupled, cut forcibly coupled and then pressed out at the same time.

27. (Amended) Method according to Claim 25 ~~or 26~~,

~~characterized in that as~~ wherein, when the plastic cards are being pressed out, ventilation is carried out which limits any effect of the air movement created by the pressure stamp on the pressing out and the direction of ejection of the plastic cards to a minimum.

28. (Amended) Method according to ~~one of the Claims 25 to 27~~,

~~characterized in that~~ wherein the pressing out of the plastic cards from the sheet or strip material is carried out by means of a peeling movement.